

Bushing Reducer
FTG x P

Job Name
Job Location
P.O.#
Engineer
Contractor
Wholesaler
Merit Associate

CarbonPress® Bushing Reducer FTG x P is available in sizes 1/2" - 2" with an EPDM or HNBR sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®)** - facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP)** - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Surface Protection:** Corrosion Resistant Zn-Ni Plating.
- **Grab Ring Deforms and Grips Outside Diameter of Pipe.**
- **Applications:** Hydronic Heating, the Conveyance of Fluids, Gases, Oils, and Low-Pressure Steam.

CarbonPress® Operational Parameters:

EPDM working pressure range from full vacuum to 250 psi (17.2 bar) for water. Working pressure range from full vacuum to 125 psi (8.6 bar) for gas.

CarbonPress® Certifications

IAPMO Z 1117 (EPDM). IAPMO/ANSI LC 4/CSA 6.32 (HNBR).

CarbonPress® Codes and Standards

IAPMO Z 1117, IAPMO/ANSI LC 4/CSA 6.32, ASME B31.1, B31.3, B31.9, CSA B149.1, UPC, and UMC.

Bushing Reducer
FTG x P

Item Number		Nominal Size		A (in)	L (in)
EPDM	HNBR	Size 1	Size 2		
MB90160	MB90161	¾"	½"	1.99	3.01
MB90165	MB90166	1"	½"	2.32	3.37
MB90170	MB90171	1"	¾"	2.26	3.50
MB90172	MB90173	1¼"	¾"	2.91	4.09
MB90175	MB90176	1¼"	1"	2.74	4.09
MB90180	MB90181	1½"	¾"	3.27	4.45
MB90185	MB90186	1½"	1"	2.87	4.25
MB90190	MB90191	1½"	1¼"	2.93	4.72
MB90195	MB90196	2"	1"	3.35	4.72
MB90200	MB90201	2"	1¼"	3.39	5.18
MB90205	MB90206	2"	1½"	3.33	5.16

