

**Coupling with Stop**
**P x P**

**Job Name**
**Job Location**
**P.O.#**
**Engineer**
**Contractor**
**Wholesaler**
**Merit Associate**

**CarbonPress® Coupling with Stop P x P** is available in sizes 1/2" - 2" with an EPDM or HNBR sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®)** - facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP)** - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Surface Protection:** Corrosion Resistant Zn-Ni Plating.
- **Grab Ring Deforms and Grips Outside Diameter of Pipe.**
- **Applications:** Hydronic Heating, the Conveyance of Fluids, Gases, Oils, and Low-Pressure Steam.

**CarbonPress® Operational Parameters:**

EPDM working pressure range from full vacuum to 250 psi (17.2 bar) for water. Working pressure range from full vacuum to 125 psi (8.6 bar) for gas.

**CarbonPress® Certifications**

IAPMO Z 1117 (EPDM). IAPMO/ANSI LC 4/CSA 6.32 (HNBR).

**CarbonPress® Codes and Standards**

IAPMO Z 1117, IAPMO/ANSI LC 4/CSA 6.32, ASME B31.1, B31.3, B31.9, CSA B149.1, UPC, and UMC.

**Coupling with Stop**
**P x P**

Item Number		Nominal Size 1	A (in)	L (in)
EPDM	HNBR			
MB90000	MB90001	1/2"	0.79	2.83
MB90005	MB90006	3/4"	0.87	3.23
MB90010	MB90011	1"	0.87	3.58
MB90015	MB90016	1 1/4"	1.12	4.72
MB90020	MB90021	1 1/2"	1.18	4.88
MB90025	MB90026	2"	1.22	5.08

