

Coupling No Stop

P x P



Job Name

Job Location

P.O.#

Engineer

Contractor

Wholesaler

Merit Associate

CarbonPress® Coupling No Stop P x P is available in sizes 1/2" - 2" with an EPDM or HNBR sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®)** - facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP)** - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Surface Protection:** Corrosion Resistant Zn-Ni Plating.
- **Grab Ring Deforms and Grips Outside Diameter of Pipe.**
- **Applications:** Hydronic Heating, the Conveyance of Fluids, Gases, Oils, and Low-Pressure Steam.

CarbonPress® Operational Parameters:

EPDM working pressure range from full vacuum to 250 psi (17.2 bar) for water. Working pressure range from full vacuum to 125 psi (8.6 bar) for gas.

CarbonPress® Certifications

IAPMO Z 1117 (EPDM). IAPMO/ANSI LC 4/CSA 6.32 (HNBR)

CarbonPress® Codes and Standards

IAPMO Z 1117, IAPMO/ANSI LC 4/CSA 6.32, ASME B31.1, B31.3, B31.9, CSA B149.1, UPC, and UMC.

Coupling No Stop		P x P	
Item Number		Nominal Size 1	L (in)
EPDM	HNBR		
MB90045	MB90046	1/2"	2.83
MB90050	MB90051	3/4"	3.23
MB90055	MB90056	1"	3.58
MB90060	MB90061	1 1/4"	4.72
MB90065	MB90066	1 1/2"	4.88
MB90070	MB90071	2"	5.08

