

Extended Coupling No Stop
P x P

Job Name
Job Location
P.O.#
Engineer
Contractor
Wholesaler
Merit Associate

CarbonPress[®] Extended Coupling No Stop P x P is available in sizes 1/2" - 2" with an EPDM or HNBR sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring[®] (VIPR[®])** - facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP)** - in addition to the VIPR[®], all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Surface Protection:** Corrosion Resistant Zn-Ni Plating.
- **Grab Ring Deforms and Grips Outside Diameter of Pipe.**
- **Applications:** Hydronic Heating, the Conveyance of Fluids, Gases, Oils, and Low-Pressure Steam.

CarbonPress[®] Operational Parameters:

EPDM working pressure range from full vacuum to 250 psi (17.2 bar) for water. Working pressure range from full vacuum to 125 psi (8.6 bar) for gas.

CarbonPress[®] Certifications

IAPMO Z 1117 (EPDM), IAPMO/ANSI LC 4/CSA 6.32 (HNBR).

CarbonPress[®] Codes and Standards

IAPMO Z 1117, IAPMO/ANSI LC 4/CSA 6.32, ASME B31.1, B31.3, B31.9, CSA B149.1, UPC, and UMC.

Extended Coupling No Stop P x P

Item Number		Nominal Size 1	L (in)
EPDM	HNBR		
MB90090	MB90091	1/2"	3.82
MB90095	MB90096	3/4"	3.98
MB90100	MB90101	1"	4.37
MB90105	MB90106	1 1/4"	5.31
MB90110	MB90111	1 1/2"	5.43
MB90115	MB90116	2"	5.63

