

Male Adapter
P x MPT

Job Name
Job Location
P.O.#
Engineer
Contractor
Wholesaler
Merit Associate

CarbonPress[®] Male Adapter P x MPT is available in sizes 1/2" - 2" with an EPDM or HNBR sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring[®] (VIPR[®])** - facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP)** - in addition to the VIPR[®], all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Surface Protection:** Corrosion Resistant Zn-Ni Plating.
- **Grab Ring Deforms and Grips Outside Diameter of Pipe.**
- **Applications:** Hydronic Heating, the Conveyance of Fluids, Gases, Oils, and Low-Pressure Steam.

CarbonPress[®] Operational Parameters:

EPDM working pressure range from full vacuum to 250 psi (17.2 bar) for water. Working pressure range from full vacuum to 125 psi (8.6 bar) for gas.

CarbonPress[®] Certifications

IAPMO Z 1117 (EPDM), IAPMO/ANSI LC 4/CSA 6.32 (HNBR).

CarbonPress[®] Codes and Standards

IAPMO Z 1117, IAPMO/ANSI LC 4/CSA 6.32, ASME B31.1, B31.3, B31.9, CSA B149.1, UPC, and UMC.

Male Adapter
P x MPT

Item Number		Nominal Size		A (in)	L (in)
EPDM	HNBR	Size 1	Size 2		
MB90675	MB90676	1/2"	1/2"	1.63	2.68
MB90680	MB90681	3/4"	3/4"	1.69	2.87
MB90685	MB90686	1"	1"	1.73	3.09
MB90690	MB90691	1 1/4"	1 1/4"	2.07	3.86
MB90695	MB90696	1 1/2"	1 1/2"	2.24	4.09
MB90700	MB90701	2"	2"	2.40	4.33

