

Reducing Tee

P x P x P



Job Name

Job Location

P.O.#

Engineer

Contractor

Wholesaler

Merit Associate

CarbonPress® Reducing Tee P x P x P is available in sizes 1/2" - 2" with an EPDM or HNBR sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®)** - facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP)** - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Surface Protection:** Corrosion Resistant Zn-Ni Plating.
- **Grab Ring Deforms and Grips Outside Diameter of Pipe.**
- **Applications:** Hydronic Heating, the Conveyance of Fluids, Gases, Oils, and Low-Pressure Steam.

CarbonPress® Operational Parameters:

EPDM working pressure range from full vacuum to 250 psi (17.2 bar) for water. Working pressure range from full vacuum to 125 psi (8.6 bar) for gas.

CarbonPress® Certifications

IAPMO Z 1117 (EPDM). IAPMO/ANSI LC 4/CSA 6.32 (HNBR).

CarbonPress® Codes and Standards

IAPMO Z 1117, IAPMO/ANSI LC 4/CSA 6.32, ASME B31.1, B31.3, B31.9, CSA B149.1, UPC, and UMC.

Reducing Tee

P x P x P

Item Number		Nominal Size			A (in)	A1 (in)	L (in)	L1 (in)
EPDM	HNBR	Size 1	Size 2	Size 3				
MB90300	MB90301	3/4"	3/4"	1/2"	1.02	0.96	2.20	2.01
MB90305	MB90306	1"	1"	1/2"	1.18	1.12	2.54	2.17
MB90310	MB90311	1"	1"	3/4"	1.18	1.18	2.54	2.36
MB90315	MB90316	1 1/4"	1 1/4"	1/2"	1.48	1.30	3.29	2.34
MB90320	MB90321	1 1/4"	1 1/4"	3/4"	1.48	1.36	3.29	2.54
MB90325	MB90326	1 1/4"	1 1/4"	1"	1.48	1.36	3.46	2.72
MB90330	MB90331	1 1/2"	1 1/2"	1/2"	1.61	1.40	3.46	2.44
MB90335	MB90336	1 1/2"	1 1/2"	3/4"	1.61	1.46	3.46	2.64
MB90340	MB90341	1 1/2"	1 1/2"	1"	1.61	1.46	3.46	2.81
MB90345	MB90346	1 1/2"	1 1/2"	1 1/4"	1.61	1.59	3.86	3.39
MB90350	MB90351	2"	2"	1/2"	1.93	1.69	3.86	2.74
MB90355	MB90356	2"	2"	3/4"	1.93	1.75	3.86	2.93
MB90360	MB90361	2"	2"	1"	1.93	1.75	3.86	3.11
MB90365	MB90366	2"	2"	1 1/4"	1.93	1.89	3.86	3.68
MB90370	MB90371	2"	2"	1 1/2"	1.93	1.91	3.86	3.76

