

# “V” SERIES



## *One* PIECE BALL VALVE

- Size Range: 1/4" - 2"
- Pressure Rating: 800 WOG
- CF8M Material
- Design Features: Blow-Out Proof Stem
- Port: Reduced
- End Type: Threaded



## *Two* PIECE BALL VALVE

- Size Range: 1/4" - 2"
- Pressure Rating: 2000/1500 WOG
- CF8M Material
- Design Features: Blow-Out Proof Stem
- End Type: Threaded



## *Two* PIECE BALL VALVE

- Size Range: 1/4" - 3"
- Pressure Rating: 1000 WOG
- CF8M Material
- Design Features: Blow-Out Proof Stem
- Port: Full
- End Type: Threaded



## *Three* PIECE BALL VALVE

- Size Range: 1/4" - 3"
- Pressure Rating: 1000 WOG
- CF8M Material
- Design Feature: Blow-Out Proof Stem
- Port: Full
- End Type: Threaded & Socket Weld



## *Class 200*

### SWING CHECK VALVE

- Size Range: 1/4" - 3"
- 200 PSI Working Pressure at 350°F
- CF8M Material
- End Type: Threaded



## *Class 200* SWING CHECK WYE PATTERN VALVE

- Size Range: 1/4" - 3"
- 200 PSI Working Pressure at 350°F
- CF8M Material
- End Type: Threaded



## *Class 200* GATE VALVE

- Size Range: 1/2" - 2"
- 200 PSI Working Pressure at 350°F
- CF8M Material
- Design Feature: Screwed Bonnet & Non-Rising Stem
- Port: Full
- End Type: Threaded



## *Class 600* Y-STRAINER

- Size Range: 1/4" - 3"
- 600 PSI Working Pressure at 350°F
- CF8M Material
- End Type: Threaded