

Ball Valve

P x P



Job Name

Job Location

P.O.#

Engineer

Contractor

Wholesaler

Merit Associate

StainlessPress® Ball Valve P x P is available in sizes ½" – 2" with an EPDM, HNBR or FKM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®)** - facilitates immediate identification of un-pressed connections.
- **Mates with IPS (Iron Pipe Size)** 304 & 316 Schedule 5 or 10 Stainless Steel Pipe
- **Leak Before Press (LBP)** - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Applications:** HVAC, plumbing, municipal, mechanical, industrial and marine applications.

StainlessPress® Operational Parameters:

- **Operating Pressure:** from full vacuum to 300 PSI on Schedule 5 or 10 Stainless Steel Pipe.
- **Temperature Range:** EPDM: -4°F to 230°F. | HNBR: -13°F to 248°F. | FKM: -4°F to 356°F.

StainlessPress® Certifications

IAPMO/ANSI/CAN Z1117, NSF/ANSI/CAN 61 (EPDM only), NSF/ANSI/CAN 372 (EPDM only), FM 1920, American Bureau of Shipping Product Design Assessment (PDA) Certificate 1-5-PR1438892-PDA, Piping System and Couplings.

StainlessPress® Codes and Standards

ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC & CMC, City of Los Angeles Plumbing & Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code: Massachusetts State Building Code 780 CMR Ninth edition: Chapter 28: NPSC, NPCC.

Ball Valve

P x P

| Ball Valve | | | | | P x P | | | | |
|--------------|---------------|---------------|-------------------|-------|-----------------|------|------|------|------------|
| Item Number | | | Nominal Size (in) | O.D. | Dimensions (in) | | | | Weight lbs |
| EPDM | HNBR | FKM | | | A | B | C | D | |
| MBF311/26GE | MBF311/26GEH | MBF311/26GEF | ½" | 0.840 | 2.82 | 4.26 | 2.44 | 4.49 | 1.24 |
| MBF313/46GE | MBF313/46GEH | MBF313/46GEF | ¾" | 1.050 | 3.50 | 5.31 | 2.68 | 5.39 | 1.73 |
| MBF3116GE | MBF3116GEH | MBF3116GEF | 1" | 1.315 | 3.86 | 5.30 | 2.75 | 5.90 | 2.46 |
| MBF3111/46GE | MBF3111/46GEH | MBF3111/46GEF | 1¼" | 1.660 | 4.17 | 6.30 | 3.35 | 6.53 | 5.90 |
| MBF3111/26GE | MBF3111/26GEH | MBF3111/26GEF | 1½" | 1.900 | 4.72 | 7.87 | 3.54 | 7.13 | 5.93 |
| MBF3126GE | MBF3126GEH | MBF3126GEF | 2" | 2.375 | 5.35 | 8.27 | 3.94 | 8.89 | 8.48 |

Operating Pressure: 300 PSI (20.7 bar)

