

Coupling w/o Stop P x P



Job Name

Job Location

P.O.#

Engineer

Contractor

Wholesaler

Merit Associate

StainlessPress® Coupling w/o Stop P x P is available in sizes ½" – 2" with an EPDM, HNBR or FKM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®)** - facilitates immediate identification of un-pressed connections.
- **Mates with IPS (Iron Pipe Size)** 304 & 316 Schedule 5 or 10 Stainless Steel Pipe
- **Leak Before Press (LBP)** - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Applications:** HVAC, plumbing, municipal, mechanical, industrial and marine applications.

StainlessPress® Operational Parameters:

- **Operating Pressure:** from full vacuum to 300 PSI on Schedule 5 or 10 Stainless Steel Pipe.
- **Temperature Range:** EPDM: -4°F to 230°F. | HNBR: -31°F to 248°F. | FKM: -4°F to 356°F.

StainlessPress® Certifications

IAPMO/ANSI/CAN Z1117, NSF/ANSI/CAN 61 (EPDM only), NSF/ANSI/CAN 372 (EPDM only), FM 1920, American Bureau of Shipping Product Design Assessment (PDA) Certificate 1-5-PR1438892-PDA, Piping System and Couplings.

StainlessPress® Codes and Standards

ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC & CMC, City of Los Angeles Plumbing & Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code: Massachusetts State Building Code 780 CMR Ninth edition: Chapter 28: NPSC, NPCC.

Coupling w/o Stop P x P

| Item Number | | | Nominal Size (in) | O.D. | Dimensions (in) | | Weight lbs |
|--------------|---------------|---------------|-------------------|-------|-----------------|------|------------|
| EPDM | HNBR | FKM | | | A | B | |
| MBF021/26GE | MBF021/26GEH | MBF021/26GEF | ½" | 0.840 | 0.83 | 2.95 | 0.18 |
| MBF023/46GE | MBF023/46GEH | MBF023/46GEF | ¾" | 1.050 | 0.95 | 3.40 | 0.25 |
| MBF0216GE | MBF0216GEH | MBF0216GEF | 1" | 1.315 | 1.02 | 3.83 | 0.34 |
| MBF0211/46GE | MBF0211/46GEH | MBF0211/46GEF | 1¼" | 1.660 | 1.18 | 4.49 | 0.46 |
| MBF0211/26GE | MBF0211/26GEH | MBF0211/26GEF | 1½" | 1.900 | 1.20 | 4.81 | 0.63 |
| MBF0226GE | MBF0226GEH | MBF0226GEF | 2" | 2.375 | 1.77 | 6.76 | 1.13 |

