


Weld Adapter	Male Weld x Female Press														
	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="background-color: #d3d3d3;">Job Name</td> <td><input type="text"/></td> </tr> <tr> <td style="background-color: #d3d3d3;">Job Location</td> <td><input type="text"/></td> </tr> <tr> <td style="background-color: #d3d3d3;">P.O.#</td> <td><input type="text"/></td> </tr> <tr> <td style="background-color: #d3d3d3;">Engineer</td> <td><input type="text"/></td> </tr> <tr> <td style="background-color: #d3d3d3;">Contractor</td> <td><input type="text"/></td> </tr> <tr> <td style="background-color: #d3d3d3;">Wholesaler</td> <td><input type="text"/></td> </tr> <tr> <td style="background-color: #d3d3d3;">Merit Associate</td> <td><input type="text"/></td> </tr> </table>	Job Name	<input type="text"/>	Job Location	<input type="text"/>	P.O.#	<input type="text"/>	Engineer	<input type="text"/>	Contractor	<input type="text"/>	Wholesaler	<input type="text"/>	Merit Associate	<input type="text"/>
Job Name	<input type="text"/>														
Job Location	<input type="text"/>														
P.O.#	<input type="text"/>														
Engineer	<input type="text"/>														
Contractor	<input type="text"/>														
Wholesaler	<input type="text"/>														
Merit Associate	<input type="text"/>														

StainlessPress® Weld Adapter Male Weld x Female Press is available in sizes ½" – 2" with an EPDM, HNBR or FKM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®)** - facilitates immediate identification of un-pressed connections.
- **Mates with IPS (Iron Pipe Size)** 304 & 316 Schedule 5 or 10 Stainless Steel Pipe
- **Leak Before Press (LBP)** - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Applications:** HVAC, plumbing, municipal, mechanical, industrial and marine applications.

StainlessPress® Operational Parameters:

- **Operating Pressure:** from full vacuum to 300 PSI on Schedule 5 or 10 Stainless Steel Pipe.
- **Temperature Range:** EPDM: -4°F to 230°F. | HNBR: -31°F to 248°F. | FKM: -4°F to 356°F.

StainlessPress® Certifications

IAPMO/ANSI/CAN Z1117, NSF/ANSI/CAN 61 (EPDM only), NSF/ANSI/CAN 372 (EPDM only), FM 1920, American Bureau of Shipping Product Design Assessment (PDA) Certificate 1-5-PR1438892-PDA, Piping System and Couplings.

StainlessPress® Codes and Standards

ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC & CMC, City of Los Angeles Plumbing & Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code: Massachusetts State Building Code 780 CMR Ninth edition: Chapter 28: NPSC, NPCC.

Weld Adapter			Male Weld x Female Press				
Item Number			Nominal Size (in)	O.D.	Dimensions (in)		Weight lbs
EPDM	HNBR	FKM			A	B	
MBF551/26GE	MBF551/26GEH	MBF551/26GEF	½"	0.840	5.13	4.30	0.62
MBF553/46GE	MBF553/46GEH	MBF553/46GEF	¾"	1.050	5.27	4.32	0.82
MBF5516GE	MBF5516GEH	MBF5516GEF	1"	1.315	5.34	4.31	0.97
MBF5511/46GE	MBF5511/46GEH	MBF5511/46GEF	1¼"	1.660	5.58	4.39	1.93
MBF5511/26GE	MBF5511/26GEH	MBF5511/26GEF	1½"	1.900	5.52	4.32	2.36
MBF5526GE	MBF5526GEH	MBF5526GEF	2"	2.375	6.09	4.31	3.70

